



tibbo.products@shagaco.com
www.shagaco.com

GP8/GP11



125Khz RFID Reader Module
GP8 without Antenna
GP11 with Antenna
RS232/Wiegand/ABA TK2
Size: 41x24x11 mm

NEW !!

DF5



Mifare DESFire Read/Write Module
13.56MHz
Size: L36 x W26 X H11.6 mm

MF5



Mifare Read/Write Module
ISO 14443A
Size: 26x36x11 mm

RWM600A



RFID Read/Write Module
13.56 MHz Smart Label
ISO 15693
Size: 39x21x11.6 mm

PA2183



RFID Reader Module
125 KHz
ABA TK2 interface

PA2713



RFID Reader Module
Mifare 13.56 MHz
Wiegand/ABA TK2

RF222



RFID Reader Module
125 KHz
TTL/Wiegand/ABA TK2
90 mm housing

MF222



RFID Reader Module
Mifare 13.56 MHz
Wiegand/ABA TK2

BCR150



Barcode Slot Reader
Without cover
TTL output
90 mm housing

BCR180



Barcode Slot Reader
With or without cover
TTL output
100 mm housing

BCR200



Barcode Slot Reader
ABA TK2 emulation
RS232, Wiegand (optional)
90 mm housing

BCR250



Barcode Slot Reader
ABA TK2 or RS232 or PS/2
100 mm housing
USB (optional)



www.shagaco.com

13.56 MHz Mifare DESFire Reader/ ISO15693 Reader

NEW !! DF700/DF710



Mifare Sector/DESFire Reader
 . DF700: Wiegand, ABA TK2, RS232
 . DF710: Wiegand, ABA TK2, RS485
 . Wall Mounting

NEW !! DF750/DF760



Mifare Sector/DESFire Reader with or without keypad
 . DF750: Wiegand, ABA TK2, RS232
 . DF760: Wiegand, ABA TK2, RS485
 . DF750K (DF760K) keypad type

SLR200



Smart Label Reader
 . 13.56MHz ISO 15693
 . Handheld type
 . USB serial or K/B emulation

SLR700



ISO15693 UID Reader
 . Wall-mounting
 . RS232/Wiegand/ABA TK2

AMP600



ISO 15693 Advanced Reader / Writer
 . Desktop or Wall-Mounting
 . RS232/RS485
 . Multi-tags reading

PCR360



ISO 15693 Reader / Writer
 . Desktop
 . USB interface

USB232



Converter
 . RS232 to USB
 . Auto baud rate switching
 up to 120K bps

USB485/USB422



Converter
 . RS485 to USB
 . RS422 to USB
 . Supports 255 devices

CON422/485



Converter
 . RS232 to RS422 /
 RS485 or RS232 to RS485
 . 1 converter supports up to 265
 devices

CON485



Converter
 . RS232 to RS485
 . 1 converter supports up to 255
 devices

CON232K



Converter
 . RS232 to Keyboard emulation

CON100iB



Multiply Interface Converter
 . Available for RS232, Wiegand,
 ABA TK2
 . Supports IButton input interface

NEW !! PS200



Power over Ether Splitter
 . One port for PoE in/the other
 port for Data out and DC5 V
 out /DC 12V out

WEC200



Wiegand to Ethernet Controller
 . 10/100 BaseT
 . Wiegand to Ethernet
 . Size:100 x 96.8 x 24.35 mm

FAT800A



Ethernet Data Terminal
 . with 16x2 LCD display
 . 20 programmable keys
 . Magstripe, Barcode, RFID
 . 10 BaseT

FAT810



Ethernet Data Terminal
 . With 16x2 LCD display
 . 20 programmable keys
 . Mag-stripe, Barcode, RFID
 . 100/10 BaseT